

65,000
SOLD TO DATE

TaxiCam_{SC}

Technical Datasheet

The TaxiCam_{SC} has been specifically designed for taxi applications where image quality and security are vital to providing an effective deterrent.

VerifEye is the industry leader with an installed base of over 65,000 taxis in more than 90 cities in over 20 countries.

Since TaxiCam is our primary business, we understand the taxi industry and the various customer/driver privacy, law enforcement and regulatory requirements better than any other provider of in-vehicle cameras.

TaxiCam installs quickly. The camera head mounts above or to the side of the rear-view mirror. The image storage unit connects to the vehicle wiring and is concealed. A downloading cable supports connection to a laptop PC or Office PC for image retrieval.



Key Features

Image Resolution

Judged the best in the industry by independent evaluations carried out by:

- State of Queensland, Australia
- City of Ottawa, Canada
- Province of British Columbia, Canada
- City of Southampton, United Kingdom
- City of Portland, United States



Robust

TaxiCam is 100% solid-state and is tolerant of power disturbances, voltage transients, mechanical shock and vibration, temperature extremes, moisture and dust.

Secure

Proprietary tamper-proof data access protocol and encrypted file storage format ensures chain-of-evidence integrity and eliminates public privacy concerns.

Efficient

Low current draw and intelligent standby power management eliminate battery drainage issues.





SINGLE CAMERA



SAMPLE IMAGE OF A ROBBERY TAKEN FROM A SINGLE CAMERA



CONTROLLER UNIT

USB "HASP" SECURITY KEY



Camera

Imaging Technology: 1/3" CCD

Illumination: 24 LEDs at 875 nm producing 60mW/m² at 2m

Single Camera: 2.9 mm, 3.6 mm or 5.5 mm (f2.0)

Connector: RJ-style with anti-tamper feature

Mounting: Lockable 2-axis adjustment; Self-adhesive mounting plate

Trigger Logic

Electrical: Selectable dry contact, active high, active low or active floating, programmable voltage trigger points

Typical Event Trigger Sources: vehicle door status circuit, taxi meter on/off, ignition, manual pushbutton, brakes, g-force

Event Response: Programmable capture sequence, fixed or variable intervals

Alarm Response: Optional pre- and post-alarm image storage with overwrite protection

Frame Rate: Up to 2 fps

Storage

Storage Media: Compact Flash, removable with security tool

Memory Size Options: 512 MB to 1GB

Recorded Information: Date/Time; Location/Speed, Taxi ID, Unit ID, Event Flags, Image Data, Audio Data

Image Compression: VerifEye proprietary (8:1)

Storage Format: VerifEye proprietary

Image capacity: 17,500 to 37,500 images

Image Security & Privacy

Image Access: USB "HASP" key for access authorization

Transfer Protocol: VerifEye proprietary

File Storage Format: Encrypted

Communication

Download: Proprietary USB connection

Setup: Proprietary USB connection

Software

VerifEye Viewer: For law enforcement agencies. Image browsing by date and time; export to JPEG, BMP and WMV; report generation.

VerifEye Installer: For authorized TaxiCam installers; Vehicle I.D. and parameter setup

VerifEye Inspector: For taxi regulatory agencies. Diagnostics for checking proper operation. Controller log and audit report generation.

Electric

Input Voltage: 11 – 15 VDC

Input Current: 800 mA max; 2mA standby

Isolation: 1,500 VRMS

Protection: Reverse-polarity, transient, over-voltage, on all connections

Dimensions

Controller: 6.4" × 4.0" × 1.4"

Single Camera: 2.75"(w) × 1.50"(h) × 2.40"(d)